MOL Arol 2T

two-stroke motor oil



MOL Arol 2T is a pre-diluted general purpose two-stoke engine oil produced from highly refined mineral base oils and additives that inhibit oxidation, corrosion, wear and deposits. The recommended mixing ratio is 1:50. The use of MOL Arol 2T is not recommended in mixture lubricated two-stroke engines working with fuels containing bio-ethanol (E85).

Application





Two-stroke premix lubricated gasoline passenger cars and motorbikes of older construction

Features and benefits

Contains a self-mixing additive

Good cleaning effect

Entirely miscible with fuel

Keeps engine parts clean and prevents spark plug fouling

Specifications and approvals

APITA

Properties

Properties	Typical values
Density at 15°C [g/cm3]	0,868
Kinematic viscosity at 20 °C [mm2/s]	76,5
Kinematic viscosity at 40°C [mm2/s]	31,0
Pour point [°C]	-24
Flash point (Cleveland) [°C]	105
Sulphated ash [mass %]	0,23

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages. In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

1 / 2 Page.

Version: 010.003.000

MOL Arol 2T

two-stroke motor oil



Ordering information

Custom Tariff Number 27101981

SAP code and packaging:

13301056 MOL Arol 2T 0,5L 13301057 MOL Arol 2T 1L 13300005 MOL Arol 2T 170KG 13301055 MOL Arol 2T 0,6 I plastic bottle 1 I plastic bottle (for order only) 216.5 I steel drum Road tank car (for order only)

Order booking:

Please contact your local distributor or sales partner for ordering details.

2 / 2 Page.

Version: 010.003.000